

Item 5B - Sustainable Management Criteria

- Subsidence
- SMC Matrix
- SW Depletion from GW Pumping - Stream Flow Cross Over Analyses


**Preliminary Draft
Subject to Revision**




Land Subsidence Evaluation

- Previous investigations and reports;
- Geodetic surveys;
- Interferometric Synthetic Aperture Radar (InSAR) data;
- Subsidence evaluations / potentials.

**Preliminary Draft
Subject to Revision**






Continuous Global Positioning Systems (CGPS)

- Geodetic surveys
- 3D positions (N-S, E-W, Elevation) every 15-30 seconds
- Four CGPS stations w/in 5 miles of basins
- Mounted on bedrock


**Preliminary Draft
Subject to Revision**

CGPS Locations and Vertical Movement Time-Series (UNAVCO)



**Preliminary Draft
Subject to Revision**


USGS 1994 NGS Leveling Routes and Measured Pre-Seismic Subsidence Rates (mm/year) from 1971 to 1989



**Preliminary Draft
Subject to Revision**


Time-Series Graphs of Annual and Total Land Surface Elevation Changes derived from InSAR

**Preliminary Draft
Subject to Revision**



InSAR Data showing Total Vertical Displacement within the Basins.

**Preliminary Draft
Subject to Revision**




Future Subsidence Potential - Representative Wells



**Preliminary Draft
Subject to Revision**


**2070CF
Modeled Water
Levels v.
Estimated
Historical Low
Water Level at
Representative
Wells**



**Preliminary Draft
Subject to Revision**

Difference between Estimated Historical Low Water Levels and 2070CF Modeled Low Water Level

**Preliminary Draft
Subject to Revision**



Summary of Subsidence Evaluations

Study / Investigator	Fillmore Basin	Piru Basin	Comments
USGS, 1996	maximum subsidence of 0.03 feet (8 mm, 0.6 mm/yr) near City of Fillmore	maximum subsidence zone up to 0.05 feet (15 mm, ~1 mm/year) around the Town of Piru	1975-1989 study period
Hanson, 2003	maximum value of just over 0.1 feet (0.00098 ft/yr) of subsidence	0.25 feet (0.0024 ft/yr) in the eastern portion of Piru Basin	1891 to 1993 study period
Ventura County, 2013 and 2020	Lies within subsidence hazard zone	Lies within subsidence hazard zone	No technical analyses conducted.
DWR, 2014	Low potential	Insufficient data	
InSAR	Less than +/-0.05 ft	Generally, less than +/-0.05 ft except during periods of artificial recharge, then up to +0.14 ft of rebound in Piru basin	June 2015 – Sept 2019 study period
2070 Climate Change Modeling by UWCD	No subsidence anticipated	No subsidence anticipated	1986 to 2096 model timeframe

Summary of (Inelastic) Subsidence Potential

Basin	Hydro-stratigraphic Setting Susceptibility	Chronic Declines in Groundwater Levels	Geodetic / Extensometer / Tiltmeter Evidence of Subsidence	InSAR Evidence of Subsidence	Subsidence Susceptibility Ranking
Fillmore	Low to Moderate	No	No	No	Low
Piru	Low	No	No	No	Low

**Preliminary Draft
Subject to Revision**



Item 5B - Sustainable Management Criteria

Water Level - Stream Flow Cross Over Analyses

- Updated relationship(s) between WLS in wells near rising GW areas and measured SW flow
- Impact of climate change on SW flows


**Preliminary Draft
Subject to Revision**






Water Level - Stream Flow Cross Over Analyses

Willard Road




Fish Hatchery





Preliminary Draft
Subject to Revision

Fish Hatchery - 04N18W31D045



Preliminary Draft
Subject to Revision



Item 5B - Sustainable Management Criteria


Groundwater Level - Rising Groundwater

- Updated relationship(s) between simulated WLs near the Fish Hatchery under the 2070CF conditions
- Impact of groundwater pumping on groundwater levels

**Preliminary Draft
Subject to Revision**



2070CF & 2070CF(No Pumping) Hydrographs - Fish Hatchery



**Preliminary Draft
Subject to Revision**

Item 5B - Sustainable Management Criteria

Minimum Thresholds & Measurable Objectives

- Updated SMC matrices

**Preliminary Draft
Subject to Revision**



SMCs - General Framework



- **Lowering GW Levels** - no chronic decline in water levels
- **Reduction of GW Storage** - no chronic decline in GW storage
- **Seawater Intrusion** - not applicable
- **Degraded Water Quality** - no regulatory authority over WQ / work with existing agencies with appropriate regulatory authority
- **Land Subsidence** - not anticipated during future climate & pumping conditions
- **Surface Water Depletion** - no chronic decline in SW flows (rising GW areas)


**Preliminary Draft
Subject to Revision**

Dry Wells Evaluation (for 2070CF Future Scenario)

Bottom line: No production wells are predicted to go dry - Only 3 AG and 2 DOM wells modelled to go dry

Notes:

- Based on comparison of modelled GW levels vs. bottom of screen...
- Some shallow monitoring wells (with screen <100 ft deep) will go dry during droughts.
- Manually inspected 3 agricultural wells and 2 domestic wells that modelled GW levels indicate would go dry:
 - Unlikely to go dry based on measured GW levels.
- Biases in modelled GW levels tends to underestimate measured GW levels making this a cautious/conservative evaluation.



**Preliminary Draft
Subject to Revision**

SMC Matrix - TBS

**Preliminary Draft
Subject to Revision**

Questions?



Preliminary Draft
Subject to Revision

